

## The high-efficiency boiler of Mark

The Mark MAXIFLEX is a very compact and sustainable high-efficiency boiler for industrial use. Available in capacities from 1400 kW to 2200 kW.

The MAXIFLEX is suitable to heat offices, garages, warehouses, apartment buildings, workshops, distribution centers and showrooms.

For a complete heating solution from Mark it is also possible to combine the MAXIFLEX boiler with water-supplied products such as the TANNER MDA and INFRA AQUA ECO.

### Benefits

- Competitive pricing
- Proven and innovative technology
- Cast aluminum heat exchanger
- Robust
- Low-noise
- Advanced diagnostic system
- Very low maintenance interval
- Low service interval
- Integrated pump control
- Closed version available
- Cascade control already integrated
- Weather-dependant control

### - Control:

- On/off thermostat
- OpenTherm
- BMS 0-10V control

The Mark MAXIFLEX is available from the end of 2018.

## Technical information

MAXIFLEX		HR 1400	HR 1800	HR 2200
Nominal input	kW	1400	1800	2200
Efficiency	%	107	107	107,5
Operating pressure	bar	6	6	6
Flue connection ø	mm	400	400	400
Weight	kg	795	968	1141
Supply voltage		230V 1F ~50 Hz		